


Series TU3 S



AVENTICS™ Series TU3 S




Spiral tubing, Series TU3-S-PAM

- suitable for dynamic laying

- Ø 6-10 mm

- Polyamide



Ambient temperature min./max.

-40 ... 80 °C

Weight

See table below

Technical data

Part No.	external	Spiral working length		Spiral internal Ø	Wall thickness
	-Ø	min.	max.		
8156060060	6 mm	0.159 m	6 m	102 mm	2 mm
8156080060	8 mm	0.208 m	6 m	102 mm	2 mm
8156100060	10 mm	0.201 m	6 m	132 mm	2 mm

Part No.	Color	Actual length	Weight per meter
8156060060	Blue	8.9 m	0.068 kg
8156080060	Blue	8.9 m	0.21 kg
8156100060	Blue	8.9 m	0.3 kg

Technical information

Halogen-free

Suitable for dynamic laying


Excellent UV resistance

Technical information

Material

Material	Polyamide
----------	-----------

Dimensions



Dimensions

Part No.	D	d_i	B max.	R	A
8156060060	6 mm	4	6 m	102 mm	0.159 m
8156080060	8 mm	6	6 m	102 mm	0.208 m
8156100060	10 mm	8	6 m	132 mm	0.201 m

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: Emerson.com/Aventics

Your local contact: Emerson.com/contactus



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2017 Emerson Electric Co. All rights reserved.
2019-03



CONSIDER IT SOLVED™